SIEMENS

# iQ500, wall-mounted cooker hood, 90 cm, Stainless steel LC97BIP50I







**The powerful wall hood convinces with a high extraction rate and an outstanding design.**

- ✓ iQdrive motor - The quiet, high-performance motor ensures efficient removal of odours and steam.
- ✓ LED light: Optimal visibility and atmosphere when cooking.
- ✓ The power level and the LED light can be selected directly – touchControl
- ✓ Pleasantly quiet - motor.
- ✓ Intensive setting with automatic after revert setting

| | |
|---|---|
| LZ00XXP00 | Long Life odor filter (replacement) |
| LZ10FXJ05 | Long Life recirculation kit |
| LZ11CXI16 | Clean Air Plus recirculation kit |
| LZ12265 | Chimney extension 1000 mm |
| LZ12365 | Chimney extension 1500 mm |
| LZ12CBI14 | Clean Air Standard recirculation kit |
| LZ12CXC56 | Clean Air Plus recirc. kit external |
| LZ12FXD51 | Long Life recirculation kit external |
| LZ31XXB16 | Clean Air Plus odor filter (replacement) |
| LZ32CBB14 | Clean Air Standard odor filter (repl.) |
| LZ50960 | Backboard 90x65cm |
| LZ50961 | Backboard 90 x 72 cm |

Typology: ..... Wall-mounted
Length electrical supply cord: ..... 130.0 cm
Height of the chimney: ..... 582-908/568-1018 mm
Height of product, without chimney: ..... 46 mm
Net weight: ..... 20.2 kg
Type of control: ..... Electronic
Number of speed settings: ..... 3-stage + 2 intensive
Maximum output air extraction: ..... 427 m³/h
Boost position output recirculating: ..... 442 m³/h
Maximum output recirculating air: ..... 343 m³/h
Boost position air extraction: ..... 702 m³/h
Number of lights: ..... 3
Noise level: ..... 55 dB(A) re 1pW
Diameter of air outlet: ..... 120 / 150 mm
Grease filter material: ..... Washable stainless steel
Odour filter: ..... No
Air circulation: ..... Convertible
Optional accessories: ..... LZ00XXP00, LZ10FXJ05, LZ11CXI16, LZ12265, LZ12365, LZ12CBI14, LZ12CXC56, LZ12FXD51, LZ31XXB16, LZ32CBB14, LZ50960, LZ50961
Type of lamps used: ..... LED
Grease filter type: ..... Multilayer cassette
Connection Rating: ..... 145 W
Fuse protection: ..... 10 A
Voltage: ..... 220-240 V
Frequency: ..... 50; 60 Hz
Plug type: ..... India plug (6 Ampere)
Type: ..... Wall-mounted
Material body: ..... Stainless steel
Plug type: ..... India plug (6 Ampere)
Dimensions of the product, with chimney (if exists) (in): ..... x x
Dimensions of the packed product: ..... 23.03 x 25.59 x 38.18
Net weight: ..... 44.000 lbs
Gross weight: ..... 59.000 lbs
Motor location: ..... Integrated motor in hood chimney
No-return airflow flap: ..... Yes
Length electrical supply cord: ..... 130.0 cm
Dimensions of the product, with chimney (if exists): ..... 614-1064 x 898.0 x 500.0 mm
Dimensions of the packed product (HxWxD): ... 585 x 650 x 970 mm
Net weight: ..... 20.2 kg
Gross weight: ..... 26.6 kg

4 242003 835432

SIEMENS

# iQ500, wall-mounted cooker hood, 90 cm, Stainless steel LC97BIP50I

**Design**
- Box design
- 90 cm stainless steel Box design hood
- For wall mounted installation
- Appliance colour: stainless steel
- Touch control with 7-segment display

**Performance**
- 3 speeds plus 2 intensive
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use427m³/h
- Intensive702 m³/h
- Extraction rate in recirculation mode:
- Max. normal use:373m³/h
- Intensive:522 m³/h
- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:
- Max. normal use:55 dB(A) re 1 pW (42dB(A) re 20 µPa sound pressure)
- Intensive:66 dB(A) re 1 pW (53 dB(A) re 20 µPa sound pressure)
- Noise levels in recirculation mode:
- Max. normal use:66 dB(A) re 1 pW (57dB(A) re 20 µPa sound pressure)
- Intensive:73 dB(A) re 1 pW (60 dB(A) re 20 µPa sound pressure)

**Comfort**
- Automatic revert setting, 6 minutes
- Automatic 10 minutes after running
- Boost function
- easy to clean innerframe
- Light dimmer function
- Softlight with dimmer function
- Efficient BLDC-technology
- 3 x 1.5W LED
- Saturation display filter: grease- and charcoal filter
- Steel filter cover
- Additional noise reduction insulation
- Back-pressure flap: Yes
- Energy Efficiency Class: A
- Average Energy Consumption: 33.8 kWh/year*
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*

**Technical Information**
- Suitable for ducted and re-circulating operation only
- Chimney hood wall fixing system
- Recirculation kit or clean air kit
- Dimensions exhaust air (HxWxD): 614-954 x 898 x 500 mm
- Dimensions recirculating (HxWxD): 614-1064 x 898 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):
- 689 x 898 x 500mm - mounting with outer chimney
- 795-1139 x 898 x 500 mm - mounting with telescopic chimney
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Total Connected load: 145 W
- Connecting cable 130 cm
- Voltage: 220 - 240 V

* In accordance with the EU-Regulation No 65/2014

SIEMENS

# iQ500, wall-mounted cooker hood, 90 cm, Stainless steel
# LC97BIP50I










